

EVERSYS E-SERIE



**ESPRESSO
SPECIALISTEN**

ESPRESSOSPESIALISTEN AS
TROMSØGATA 5B
0565 OSLO, NORGE
+47.46.96.96.96
POST@ESPRESSOSPESIALISTEN.NO
WWW.ESPRESSOSPESIALISTEN.NO

Gjennom innovativ teknologi og en konstruksjon utelukkende basert på komponenter av svært høy standard lager produsenten fra Sveits ikke bare allsidige og driftssikre modeller; de lager superautomatiske espressomaskiner som legger seg tett opptil standarden på tradisjonelle maskiner.

Gjennom ETC (Extraction Time Control) har Eversys satt en ny bransjestandard hva gjelder konsistente drikker. Gjennom modulbasert design reduseres eventuell nedetid til et minimum.

	E'2	E'4	E'6
Hourly productivity Espresso or Hot water emilk system	175+ espresso (23s extraction time) & 150 hot water (2.0dl hot water portions) & continuous steam supply 175+ cappuccino	350 espresso (23s extraction time) & 150 hot water & continuous steam supply or 350 cappuccino	525 espresso (23s extraction time) & 150 hot water & continuous steam supply or 350 cappuccino
Bean hopper capacity	2 x 0.6...1.5 kg	2 x 0.6...1.5 kg	4 x 1.5kg
Brew chamber capacity	1 x up to 24 g	2 x up to 24 g	3 x up to 24g
Coffee spout height	65...165 mm	65...165 mm	65...165 mm
User interface	1 x 8" Colour Touch Screen	2 x 8" Colour Touch Screen	3 x 8" colour touch screen
Lighting front	Full colour LED, all colours and colour gradient adjustable	Full colour LED, all colours and colour gradient adjustable	Front panel full colour LED
Communication interfaces	USB, SD-Card, Ethernet, Serial RS-232, CCI	USB, SD-Card, Ethernet, Serial RS-232, CCI	USB, SD-Card, Ethernet, Serial, RS-232, CCI
Power requirement Single-phase Two-phases Three-phases	1/N/PE, 220-240V~, 50/60Hz, 25A, 5.8kW 2/PE, 200-210V~, 50/60Hz, 30A, 4.9kW 3/N/PE, 380-420V~, 50/60Hz, 15A, 9.6kW	1/N/PE, 220-240V~, 50/60Hz, 25A, 5.8kW 2/PE, 200-210V~, 50/60Hz, 30A, 4.9kW 3/N/PE, 380-420V~, 50/60Hz, 16A, 9.6kW	1/N/PE, 220-240V~, 50/60Hz, 25A, 5.8kW 2/PE, 200-210V~, 50/60Hz, 30A, 4.9kW 3/N/PE, 380-420V~, 50/60Hz, 15A, 9.6kW
Standby consumption	less than 2 W	less than 2 W	less than 2 W
Water connection	Stainless steel braided hose L: 2 m with screw-top G3/8", 0...4 bar	Stainless steel braided hose L: 2 m with screwcap G3/8", 0...4 bar	Stainless steel braided hose L: 2 m with screwcap G3/8", 0...4 bar
Drain	Drain hose ø 23 mm, l = 2 m	Drain hose ø 23 mm	Drain hose ø 23 mm
Water quality Total hardness Carbonate hardness pH value	5...8°dH max. 6°KH ideal 7.0...7.2	5...8°dH max. 6°KH ideal 7.0...7.2	5...8°dH max. 6°KH ideal 7.0...7.2
Weight	approx. 83 kg, 87 kg with fridge	approx. 90 kg, 94 kg with fridge	approx. 330 kg
Dimensions	560 mm x 600 mm x 713 mm (W x D x H) 840 mm x 600 mm x 713 mm (W x D x H) (fridge)	560 mm x 600 mm x 713 mm (W x D x H) 840 mm x 600 mm x 713 mm (W x D x H) (fridge)	840 mm x 713 mm x 600 mm (W x D x H)

Teknologi

e'Connect

Et ledende telemetrisystem som lar deg følge og prosessere live data om maskinen fra hvor som helst i verden. Det gir mulighet for å kontrollere konsistens og ytelse, sikre transparens, optimalisere service på maskinen og generere statistikk.

e'Clean

Eversysmaskiner kan lagre en måneds beholdning av rensetabletter, som blir matet ut daglig for å sikre optimal ytelse på maskinen.